



SPECIFICATIONS SHEET



FARGO® HDP5000

Print Method:	HDP® Dye-Sublimation / Resin Thermal Transfer
Resolution:	300 dpi (11.8 dots/mm)
Colors:	Up to 16.7 million / 256 shades per pixel
Print Ribbon Options:	<ul style="list-style-type: none"> • Full-color, YMC*, 750 prints • Full-color with resin black, YMCK*, 500 prints • Full-color with two resin black panels, YMCKK*, 500 prints, • Full-color with resin black and heat seal panel for difficult-to-print surfaces, YMCKH*, 500 prints • Full-color with resin black and inhibit panel for signature or other non-printing areas, YMCKI*, 500 prints • Full-color with fluorescing and resin black, YMCFK*, 500 prints • Resin black, K, 3000 prints
HDP Film Options:	• Clear (1,500 prints) • Standard Holographic (500 prints) • Custom Holographic, special order (500 prints)
Overlamine Options:	<ul style="list-style-type: none"> • Thermal Transfer Overlamine, .25 mil thick, 500 prints • PolyGuard® Overlamine, 1.0 mil and .6 mil thick, 250 prints (PolyGuard available in a CR-80 patch size) All overlaminates available in clear, standard holographic design or custom holographic design
Print Speed:**	Batch Mode: <ul style="list-style-type: none"> • Up to 24 seconds per card / 150 cards per hour (YMC with transfer)* • Up to 29 seconds per card / 124 cards per hour (YMCK with transfer)* • Up to 40 seconds per card / 90 cards per hour (YMCKK with transfer)* • Up to 35 seconds per card / 102 cards per hour (YMCK with transfer and dual-sided, simultaneous lamination)* • Up to 48 seconds per card / 75 cards per hour (YMCKK with transfer and dual-sided, simultaneous lamination)*
Accepted Standard Card Sizes:	CR-80 (3.370"L x 2.125"W / 85.6mmL x 54mmW)
Print Area:	Over-the-edge on CR-80 cards
Accepted Card Thickness:	<ul style="list-style-type: none"> • Print only: .030" (30 mil) to .050" (50 mil) / .762mm to 1.27mm • Print/Lamination: .030" (30 mil) to .050" (50 mil) / .762mm to 1.27mm
Accepted Card Types:	ABS, Laminated PVC, PET, PETG, proximity, smart and mag stripe cards Note: ABS and PVC cards are not recommended for use in the HDP5000 Lamination Module.***
Input Card Cartridge Capacity:	100 cards (.030" / .762mm)
Output Hopper Card Capacity:	200 cards (.030" / .762mm)
Card Cleaning:	Replaceable cleaning roller (included with each print ribbon)
Display:	Graphical OLED
Software Drivers:	Windows® 10 / 8.1 / 8 / 7 / Vista® / XP / Server 2012 / Server 2012 R2 / Server 2008 / Server 2008 R2 / Server 2003
Single Wire USB 2.0 Encoding Options:	<ul style="list-style-type: none"> • ISO Magnetic Stripe Encoding, dual high- and low-coercivity, Tracks 1, 2 and 3 • Contactless Smart Card Encoder (HID iCLASS® and MIFARE) • ISO 7816 Contact Smart Card Encoder • Prox Card Reader (HID read-only)
Interface:	USB 2.0 (high speed) and Ethernet with internal print server
Operating Temperature:	65° to 90° F / 18° to 32° C
Humidity:	20 - 80% non-condensing
Dimensions:	<ul style="list-style-type: none"> • HDP5000: 11.50"H x 12.25"W x 9.25"D / 292mmH x 313mmW x 235mmD • HDP5000 + Dual-Sided Module: 11.50"H x 17.50"W x 9.25"D / 292mmH x 445mmW x 235mmD • HDP5000 + Single-Sided Lam Module: 12.75"H x 25"W x 9.25"D / 324mmH x 635mmW x 235mmD • HDP5000 + Dual-Sided Module + Dual-Sided Lam Module: 12.75"H x 30"W x 9.25"D / 324mmH x 762mmW x 235mmD • Lam Module: 12.75"H x 12.25"W x 9.25"D / 324mmH x 313mmW x 235mmD
Weight:	• HDP5000: 16 lbs. / 7.3 kg, HDP5000 + Dual-Sided Module: 22 lbs. / 10 kg, HDP5000 + Single-Sided Lam Module: 28 lbs. / 12.7 kg, HDP5000 + Dual-Sided Module + Dual-Sided Lam Module: 36 lbs. / 16.4 kg
Certifications:	UL, CE, IC, FCC Class-A, CCC, BSMI, KC, MIC
Supply Voltage:	100-240 VAC, 3.3A
Supply Frequency:	50 Hz / 60 Hz
Warranty:	• Printer - Three years including one year of free printer loaner support (U.S. only); optional Extended Warranty Program (U.S. only), Printhead - Lifetime; unlimited pass
FARGO Secure Materials:	FARGO Card Printer/Encoders require highly specialized media to function properly. To maximize printed card quality and durability, printhead life and printer/encoder reliability, use only HID Secure Materials. HID warranties are void, where not prohibited by law, when non-HID Secure Materials are used.
Options:	• Dual card input hopper module • Card lamination module - single-sided or dual-sided (simultaneous)*** • Magnetic stripe encoding • 200-card input hopper • Smart card encoding (contact/contactless) • Dual-sided printing • Door and cartridge locks • Printer cleaning kit • Secure proprietary consumables system • Custom secure holographic HDP Film and overlamine
Software:	FARGO Workbench diagnostic utility with Color Assist spot-color matching

* Indicates the ribbon type and the number of ribbon panels printed where Y=Yellow, M=Magenta, C=Cyan, K=Resin Black, I=Inhibit, F=Fluorescing, H=Heat Seal
 ** Print speed indicates an approximate print speed and is measured from the time a card drops into the output hopper to the time the next card drops into the output hopper. Print speeds do not include encoding time or the time needed for the PC to process the image. Process time is dependent on the size of the file, the CPU, amount of RAM and the amount of available resources at the time of the print.
 *** ABS and PVC cards are not recommended for use in the HDP5000 Lamination Module. (Free card proofing available. Please contact your local integrator for more information.)



North America: +1 512 776 9000
 Toll Free: 1 800 237 7769
 Europe, Middle East, Africa: +44 1440 714 850
 Asia Pacific: +852 3160 9800
 Latin America: +52 55 5081 1650

ASSA ABLOY
 An ASSA ABLOY Group brand

© 2019 HID Global Corporation/ASSA ABLOY AB. All rights reserved. HID, HID Global, the HID Blue Brick logo, the Chain Design, iCLASS, HDP and FARGO are trademarks or registered trademarks of HID Global or its licensor(s)/supplier(s) in the US and other countries and may not be used without permission. All other trademarks, service marks, and product or service names are trademarks or registered trademarks of their respective owners.
 2019-02-21-si-hdp5000-printer-spec-en PLT-00069